

# LG-ITR2C-553924

## DATA SHEET

SPEC.NO.: SZ19090505  
DATE: 2019/09/09  
REV. A/0

Approved By:

Checked By:

Prepared By:

## ■ Features

- Fast response time
- High analytic
- Cut-off visible wavelength  $\lambda = 940\text{nm}$
- High sensitivity
- Pb free
- The product itself will remain within RoHS compliant version

## ■ Descriptions

The LG-ITR2C-553924 consist of an infrared emitting diode and an NPN silicon phototransistor, encased side-by-side on converging optical axis in a black Thermoplastic

Housing The phototransistor receives radiation from the IRED only .This is the normal Situation. But when an object is in between , phototransistor could not receives the radiation.

## ■ Applications


- Mouse Copier
- Switch Scanner
- Floppy disk driver
- Non-contact Switching
- For Direct Board

## ■ Device Selection Guide

Device No.	Chip Material	LENS COLOR
IR	GaAlAs	Water Clear
PT	Silicon	Black


# LIGHT

■ Package Dimension




## Notes:

1. All dimensions are in millimeters.
2. Tolerances unless dimensions  $\pm 0.25\text{mm}$ .
3. Lead spacing is measured where the lead emerge from the package.



01



0 60 80 100  
ature (°C)


0 0

0.2

0.4 0.2


70  
80

0



50 75 85 100

Temperature Ta (°C )



40

Amb